

Quotation

To

Company : Siemens AG
City / Country : Duisburg / Germany
Name : Stoverink Simon
Dept :
Tel :
Fax :
E-mail :

Name : N. HOST
Dept : Sales Dept.
Tel : +33 (0)3 69 20 51 50
Fax : +33 (0)3 88 67 60 75
E-mail : nhost@flender-graff.com
Page(s) : 19
Copy :
Date : 16.03.2016

Y/ref : Khursaniyah Al Fadhili - D43-K-1801 -
O/ref : D41104 quotation number 3

In response to your inquiry referenced above, we are pleased to confirm our quotation as follows :

ITEM A 1 : Flender Graffenstaden (FG) High Speed increaser, model **TX50/4C**

- *Rating conditions :* Rated power at **6800 kW**
Driven by a electric motor at **1800.0 rpm** (specified : 1800.0 rpm)
Driving a centrifugal compressor at **7309.1 rpm** (specified : 7285.0 rpm)
Service factor **1.45** according to **API613/03** (required : > 1.4)
- *Technical description :* Double helical
Manufacturing according to API standard
Flange on LS shaft end
Flange on HS shaft end
Estimated Weight : 4000 kg
- *Bearings description :* 2 cylindrical bearings on LS shaft
2 offset bearings on HS shaft
1 double acting tilting pad thrust bearing on low speed shaft non driven end
- *Mechanical running test :* Full speed, no load test during 4 hours according to the API 613 5th Edition standard.
- *Lubrication conditions :* 164 l/min of Oil ISO VG 46 at 60°C and 2.5 bar at inlet (calculated values only)
- *Miscellaneous:* Efficiency at full load : 99.03 %
Power losses at full load : 66 kW (calculated value only)
Anticipated Sound Pressure Level: 82.0 ± 2dB(A) at 1 meter

Base price : **117 900 EUR** each gear box
Delivery time : **36 weeks** after the FG acknowledgement of the order
Quantity : **8 gearboxes**

Comments :

- Coupling data taken into account on HS Shaft:
 - o Weight: 26.6 kg
 - o Center of gravity position from shaft end: 30.9 mm
 - o Inertia: 0.266 kgm²
- Coupling data taken into account on LS Shaft:
 - o Weight: 87.5 kg
 - o Center of gravity position from shaft end: 40.9 mm
 - o Inertia: 0.875 kgm²

Including :

- Customer witness of test
- After test disassembly and inspection
- Noise level test report
- Lateral analysis undamped
- Documentation : downloadable electronic file in english

Instrumentation (see the complete package on additional technical data sheet):

- *Temperature package*
12 RTD's PT100 Duplex 3 wires from Thermo Electric Company Inc.
(2 per bearing and thrust bearing side) not wired with terminal heads..... Price included
- *Bently Nevada vibration package*
8 radial (4 per shaft) & 2 axial (on LS shaft) vibration probes, 2 accelerometers (1 per shaft), 2
keyphasors (1 per shaft) not wired Price included

Spare parts (Prices are net valid only if spares are ordered together with the gearbox):

- *Commissioning Spares*
2 RTD's, 2 BN vibration probes, 2 BN accelerometers 7 900 EUR Lot Net
- *2 Years Normal Operation Spares*
2 set of bearings with RTD's, 1 set of oil seals 48 420 EUR Lot Net
- *Strategic Spare Parts*
One complete set of rotating elements consisting of one pinion and one gear.
Tested if ordered together with the main gearbox according to API613/03
Full Speed, No Load, with Test Report..... 51 500 EUR Lot Net
- *Container for horizontal spare rotors storage painted according FG standard..... 17 100 EUR Lot Net*

SPECIAL PURPOSE GEAR UNITS
API 613 FIFTH EDITION
DATA SHEET SI UNITS

Job No. 41104 Item No. A
P.O. No. _____ Date _____
Requisition No. _____
Inquiry No. _____
Revision 1 Date 06.03.2015 By HNI

1 Applicable To: ☒ Proposal ☐ Purchase ☐ As Built 2 For <u>Siemens AG Dulsburg</u> 3 Site <u>Khursanlyah Al Fadhill</u> 4 Unit <u>STC-SV 08-4-A</u> 5 Service <u>EM/CC</u> 6 No. required <u>9</u>	☐ US Standards (1.7) ☒ ISO Standards (1.7) Manufacturer <u>FLENDER-GRAFFENSTADEN</u> Model No. <u>TX50/4C</u> Serial No. _____ Driver type <u>electric motor</u> Driven equipment <u>centrifugal compressor</u>
NOTE : Numbers within () refer to applicable API standard 613 paragraphs ☐ Information to be completed by purchaser ☐ Information to be completed by manufacturer	
○ UNITS OF MEASUREMENT ☐ US Customary units ☒ SI units ○ RATING REQUIREMENTS Driven equip. (2.1.4): Norm. _____ Max _____ kW Driver: Rated _____ Max _____ kW Normal transmitted power (2.2.2) _____ kW Gear unit rated power (2.2.1) <u>6800</u> kW Torque @ max cont speed _____ Nm Max torque (2.2.1) _____ Nm @ _____ rpm ☐ Reducer ☒ Increaser Rated speed (2.1.5): Input <u>1800</u> rpm ☐ Specified ☒ Nominal Output <u>7285</u> rpm ☐ Specified ☒ Nominal Allow var in gear ratio (2.1.6) (+) (-) _____ % Max continuous speed (1.5) <u>1800 / 7285</u> rpm Trip speed (1.5) (2.1.7) <u>1980 / 8013,5</u> rpm Gear service factor (2.2.3.1) <u>1,4 API 613/2003 5 TH</u> (min) Hardness (2.2.3.2) Pinion _____ Gear _____ Shaft assembly designation (2.1.10) _____ L/R HS shaft rot fac'g cpl'g (2.1.20.2) ☒ CW ☐ CCW LS shaft rot fac'g cpl'g (2.1.20.2) ☒ CW ☐ CCW External loads (2.1.16) _____ Other operating conditions (2.2.2) (2.6.1.3) _____ ○ INSTALLATION DATA (2.1.14) ☐ Indoor ☐ Heated ☐ Under roof ☒ Outdoor ☐ Unheated ☐ Partial sides ☐ Grade ☐ Mezzanine ☒ ONSHORE ☐ Winterization required ☐ Tropicalization required Electrical area (2.1.10) Class _____ Grp _____ Div _____ Electrical area (2.1.10) Zone <u>2</u> Grp <u>IIA</u> Temp <u>T1</u> °C Max allow SPL (2.1.6) _____ dB(A) @ _____ m Elevation _____ m Barometer _____ kPa abs Range of ambient temperatures: Dry bulb _____ °C Wet bulb _____ °C Normal _____ °C Maximum <u>82</u> °C Minimum <u>0</u> °C Unusual conditions ☐ Dust ☐ Fumes ☐ _____	■ BASIC GEAR DATA ☒ Single stage ☐ Single helical ☐ Double stage ☒ Double helical ☐ Epicyclic ☐ horizontal offset Mechanical rating (1.5.16) <u>9520</u> kW @ <u>1800 / 7309,1</u> rpm Gear service factor (2.2.3.1) <u>1,44</u> API 613/2003 5 TH (actual) Full load gear unit power loss <u>66</u> kW Gear Unit Mechanical efficiency <u>99,03</u> % Rating speed Pinion <u>7,309,1</u> Gear <u>1,800,0</u> rpm Hardness used for Rating, (HB or Rc) Pinion <u>58 HRC</u> Gear <u>58 HRC</u> Tooth pitting index, "K" (2.2.4.1) (2.2.4.2) Allowable <u>2,17</u> Actual <u>2,10</u> MPa Material index number (Fig 3, Table 4) <u>3,03</u> MPa Bending stress number, "S_t" (2.2.5.1) (2.2.5.2) Pinion: Allowable <u>265,4</u> Actual <u>256,0</u> MPa Gear: Allowable <u>265,4</u> Actual <u>240,9</u> MPa Pitch line velocity <u>77,1</u> m/s Anticipated SPL (2.1.6) <u>82</u> dB(A) @ <u>1</u> m WR² referred to LS shaft <u>126,12</u> kgm² Breakaway torque <u>412</u> Nm @ LS Shaft Pinion teeth hardness range <u>58 - 63 HRC</u> Pinion teeth hardening method <u>CARBURIZED</u> ☐ HS shaft separate hardness range _____ Gear teeth (rim) hardness range <u>58 - 63 HRC</u> Gear teeth hardening method <u>CARBURIZED</u> Gear hub: ☒ Forged cylinder ☐ Forged & Copped ☐ Fabricated Gear to Shaft fit method (2.5.3.2) ☐ Integral ☐ Keyed interference ☒ Keyless interference Rim attachment (2.5.3.2) <u>FORGED GEAR WHEEL</u> LS shaft hardness range <u>HB 230 - 274</u> Journal static weight loads (2.6.6.3) Pinion <u>128 / 42</u> kg Gear <u>942 / 707</u> kg Total gear unit assembled weight <u>4000</u> kg NOTES: _____ _____ _____

SPECIAL PURPOSE GEAR UNITS
API 613 FIFTH EDITION
DATA SHEET SI UNITS

■ GEAR DATA				○ COUPLINGS AND GUARDS		
		Pinion	Gear		Pinion	Gear
Number of teeth	33		134	Coupling furnished by (3.2.1)	Compr. Supplier	Compr. Supplier
Gear ratio	4,06			Mount coupling halves (3.2.2)	Compr. Supplier	Compr. Supplier
Tangential load, "Wt" (2.2.4.2)	88,155	N		Cplg. guard adapter by (3.2.3)	Gear Supplier	Gear Supplier
AGMA Geometry factor "J"	0,55		0,57	Cplg. guard furnished by (3.2.3)	Compr. Supplier	Compr. Supplier
Pitch diameter	201,56		818,44	Coupling vendor (3.2.3)		
Outside diameter	214,10		827,60	Vendor's model number (3.2.3)		
Root diameter	187,25		800,74	Coupling weight on shaft, kg	26,6	87,5
Center groove diameter	177,00		790,00	CG Inboard / outboard of shaft end	Outboard	Outboard
Normal pressure angle	20,00	deg		Hub drill template provided	☐	☐
Normal diametral pitch	4,62	in ⁻¹		■ SHAFT END DETAIL (2.5.4.2)		
Helix angle	25,00	deg		Shaft end detail specified by: ☒ Purchaser ☐ Gear vendor		
Center distance	510,00	mm		(Integral unless otherwise specified)		
Backlash min	0,34	mm		Shaft end detail if 'otherwise' specified:		
Net face width, "Fw"	260,00	mm		Tapered / Keyless	☐ ☐	☐ ☐
Pinion L/D	1,71			Tapered / 1-Key	☐ ☐	☐ ☐
Face overlap ratio	6,36			Tapered / 2-Keys	☐ ☐	☐ ☐
Transverse contact ratio	1,45			Cylindrical / 1-Key	☐ ☐	☐ ☐
AGMA 6011 service factor	2,64			Cylindrical / 2-Keys	☐ ☐	☐ ☐
Rating based on ANSI/AGMA 6011 with SF=1.0				Other <u>Flanged</u>	☒ ☐	☒ ☐
Durability Power	21442	kW		Shaft diameter	120,0	190,0 mm
Strength Power	17946	kW		(If integral flange use diameter immediately adjacent to flange)		
Tooth Surface Finish, Ra	0,4	µm	0,4	■ RADIAL BEARINGS		
Tooth Generation Process	Hobbing		Hobbing	Type	OFFSET / OFFSET	CYL. / CYL.
Tooth Finishing Process	Grinding		Grinding	Diameter	130 / 130	200 / 200 mm
Lead modification (2.2.4.6)	☒ Not Req'd		☐ Req'd	Length	130 / 130	100 / 100 mm
Calculated Total Lead Mismatch		µm		Journal velocity	49,8 / 49,8	18,8 / 18,8 m/s
■ SCUFFING DATA (2.2.6)				Loading	2,78 / 2,81	2,87 / 2,71 Nmm ²
Scuffing Data per ANSI/AGMA 926-A03				Clearance (min-max)		mm
Scuffing Risk (2.2.6) <=5% (Low)		Calculation Method	AGMA925	Span	550	550 mm
Composite surface roughness, α_x	0,57	µm		Power loss each bearing	13,8 / 13,8	3,0 / 3,0 kW
Specific film thickness, EHL λ_{min}	3,31	µm		Oil flow each bearing	42,0 / 42,0	10,0 / 10,0 l/min
Tooth temperature, θ_m	82	°C		■ THRUST BEARINGS		
Maximum contact temperature, θ_{Bmax}	101	°C		Location		OPP.CPLG.SIDE
■ MATERIALS				Manufacturer	FLENDER	FLENDER
Gear casing	Steel	Oil seals	aluminium	Type	NO	COMB.TAP.LANDS
Pinion(s)	18CrNiMo7-6			Size		BPK LEG 6"
Gear rim(s)	18CrNiMo7-6			Area		11615 mm ²
HS Shaft	Integral	LS Shaft	42CrMo4	Loading		1,14 MPa
Radial bearings	Babbitt	Backing	Steel	Rating		1,50 MPa
Thrust bearing(s)	Babbitt	Backing	Steel	Int. thrust load		N
○ SHAFT END DETAIL				Ext. thrust load	4,050	9,200 N
☒ Gear shaft end for coupling integral flange (2.5.4.2)				Power loss each	0,0	6,0 kW
☒ Pinion shaft end for coupling integral flange (2.5.4.2)				Oil flow each bearing	0,0	20,0 l/min
☐ Other:	WITHOUT BOLTS			NOTES:		

SPECIAL PURPOSE GEAR UNITS
API 613 FIFTH EDITION
DATA SHEET SI UNITS

SPECIAL PURPOSE GEAR UNITS API 613 FIFTH EDITION DATA SHEET SI UNITS ☐ Oil system furnished by (2.8.3) _____ ☐ Other _____ ☐ Gear vendor _____ ☐ Oil visc. _____ cp @ 40°C _____ cp @ 100°C (2.8.6) ☐ ISO Grade _____ Load stage (2.2.6) 5,0 ■ MESH Mesh and windage power loss 26,4 kW Oil flow, mesh 40,0 l/min ■ LUBRICATION REQUIREMENTS Min. startup oil temperature 20,0 °C Normal oil inlet temperature 60,0 °C Maximum oil inlet temperature 65,0 °C Unit oil flow (total) 164,0 l/min Unit oil pressure 2,5 bar ☐ Oil visc. _____ cp @ 40°C _____ cp @ 100°C (2.8.6) ☐ ISO Grade 46 Load stage (2.2.6) 5,0 ■ PIPING CONNECTIONS <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Service</th> <th>No.</th> <th>Size</th> <th>Type</th> </tr> </thead> <tbody> <tr> <td>Lube oil inlet</td> <td>1</td> <td>2 in.</td> <td>ANSI 150 LBS</td> </tr> <tr> <td>Lube oil outlet</td> <td>1</td> <td>6 in.</td> <td>ANSI 150 LBS</td> </tr> <tr> <td>Casing drain *</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Vent</td> <td>1</td> <td>1,5 in.</td> <td>ANSI 150 LBS</td> </tr> <tr> <td>Casing purge</td> <td></td> <td></td> <td></td> </tr> </tbody> </table> * Casing drain is 'dead bottom' housing drain, not lube oil outlet ○ MOUNTING PLATES ☐ Gear furnished with (3.3.1.1) ☐ Baseplate ☐ Soleplate ☐ Subplate(s) (3.3.2.10) ☐ Mounting plates(s) furnished by (3.3.1.1) _____ ☐ Baseplate leveling (3.3.2.3) _____ ☐ Baseplate with leveling pads (3.3.2.3) ☐ Baseplate suitable for column mounting (3.3.2.4) ☐ Vendor review of purchaser's foundation dwgs. (2.1.13) ☐ Grout type (3.3.1.2.4) _____ ○ CONTRACT DATA ☐ Test data prior to shipment _____ ☒ Progress report (5.3.3) _____ ☐ Vendor signoff of Inspector checklist (4.1.1.3) ☒ Information retained for 20 years (4.2.1.1) (4.2.2.6.1) ☐ Technical manual (5.3.5.4) ☒ PAINTING (4.4.3.1) ☒ Flender standard RAL5015 (blue) ☒ Painting housing interior not allowed (2.3.1.14) ○ SHIPMENT ☐ Steel rotor storage container (4.4.5) ☐ Shaft covers (4.4.4) Contract unit Spares Export boxing ☐ ☐ Domestic boxing ☐ ☐ Outdoor storage over 6 mos. ☐ 3 years Indoor ☐ (4.4.3.8) Job No. 41104 Item No. A P.O. No. _____ Date _____ Requisition No. _____ Inquiry No. _____ Revision 1 Date 06.03.2015 By HNI ○ ADDITIONAL REQUIREMENTS ○ VIBRATION DETECTORS RADIAL (3.4.2.1) (2.7.4.5) (2.7.4.6) ☒ Manufacturer BENTLY NEVADA ☒ Total No. 8 ☒ X-Y probes pinion bearings ☒ Coupling end ☒ Blind end ☒ X-Y probes gear bearings ☒ Coupling end ☒ Blind end ☐ Other _____ AXIAL (3.4.2.1) (2.7.4.5) (2.7.4.6) ☒ Manufacturer BENTLY NEVADA ☒ Total No. 2 ☐ Dual probes at each thrust bearing ☐ Single probe any shaft without thrust bearing ☐ Other _____ ONE EVENT PER REVOLUTION PROBE (2.7.4.5) (2.7.4.6) ☒ Manufacturer BENTLY NEVADA Total No. 2 ☒ One on input shaft ☒ One on output shaft ☐ Other _____ ACCELEROMETER (3.4.2.1) (2.7.4.5) (2.7.4.6) ☒ Manufacturer BENTLY NEVADA ☒ No. required 2 ☒ Pinion coupling end ☒ Gear coupling end ☐ Other _____ ○ TEMPERATURE DETECTORS ☐ Dial type thermometers (3.4.2.7) _____ ☒ Type brg. temp. sensors (3.4.2.7) (2.7.1.3) PT100 ☐ RTD ☐ Thermocouple / ☐ Simplex ☒ Duplex Calibration Yes ☒ HS/LS bearings no. sensors each 2 / 2 ☒ Thrust number of sensing elements each face 2 ○ OTHER VIBRATION AND TEMPERATURE (3.4.2.5) (3.4.2.6) Other Gear vendor Oscillator demodulator supplied by ☐ ☒ Vibration monitor supplied by ☒ ☐ ☐ Vibration shutdown delay time _____ seconds Temperature monitor supplied by ☒ ☐ Oscillator demodulator J-box by ☒ ☐ Temp. sensor termination J-box by ☒ ☐ J-box type _____ Mount _____ ○ MISCELLANEOUS ☒ Undamped critical analysis report (2.6.2.1) ☐ w/ dampd rotr respsn analys rpt (2.6.2.4.3) (2.6.2.6) Torsional analysis by (2.6.5.2) ☐ Gear vendor ☒ Other ☐ Spare set of gear rotors (4.3.2.4) ☐ Gear case furnished with inlet purge connection (2.4.3) ☐ Orientation of oil inlet & drain conns. (2.4.6) ☒ Filter breather location (2.3.1.12) Prov. on upper casing ☐ Torsional device provisions (2.5.4.5) _____ ☐ Rotor vertical storage provisions (2.5.4.8) _____ ☐ Rotor vertical storage fixture(s) (3.6.2) _____ ☐ Vendor service rep. on site (2.1.13) _____	Service	No.	Size	Type	Lube oil inlet	1	2 in.	ANSI 150 LBS	Lube oil outlet	1	6 in.	ANSI 150 LBS	Casing drain *				Vent	1	1,5 in.	ANSI 150 LBS	Casing purge			
Service	No.	Size	Type																					
Lube oil inlet	1	2 in.	ANSI 150 LBS																					
Lube oil outlet	1	6 in.	ANSI 150 LBS																					
Casing drain *																								
Vent	1	1,5 in.	ANSI 150 LBS																					
Casing purge																								

SPECIAL PURPOSE GEAR UNITS
API 613 FIFTH EDITION
DATA SHEET SI UNITS

Job No. 41104 Item No. A
P.O. No. _____ Date _____
Requisition No. _____
Inquiry No. _____
Revision 1 Date 06.03.2015 By HNI

O INSPECTIONS AND TESTS (4.1)				
	Req'd	Witness	Observe	Test Log
☐ Advance notice of witness testing required (4.1.3)				
Number calendar days _____				
Shop Inspection (4.1.1)	☐	☐	☐	
Cleanliness Inspection (4.2.3.1)	☐	☐	☐	
Hardness Verification (4.2.3.3)	☒	☐	☐	☒
Dismantle-reassembly (4.3.2.3.1)	☒	☐	☐	☐
Contact Check (2.5.2.2)	☒	☐	☐	☐
Contact Check Tape Lift (2.5.2.2)	☒	☐	☐	☒
Gear accuracy check (2.5.2.1)	☒	☐	☐	☐
Double helical axial stability (2.5.2.3)	☒	☐	☐	☒
Special testing Integral forged gears (2.5.3.3)				
(testing per mutual agreement)	☐	☐	☐	☐
Residual unbalance check (2.6.6.2)	☒	☐	☐	☒
Mechanical Run Test (Main) (4.3.2)	☒	☐	☐	☒
Mechanical Run Test (Spare) (4.3.2.4)	☐	☐	☐	☐
Addl. Mechanical Tests (4.3.2.2.16)	☐	☐	☐	☐
Part or Full Load And Full Speed				
Test (4.3.3.1)	☐	☐	☐	☐
Full torque, reduced speed (4.3.3.2)	☐	☐	☐	☐
Full Torque Static Test (4.3.3.3)	☐	☐	☐	☐
Back-To-Back Locked Torque				
Test (4.3.3.4)	☐	☐	☐	☐
Sound Level Test (4.3.3.5)	☒	☐	☐	☒
Additional gear tooth test (4.2.2.8)	☐	☐	☐	☐
Use shop Lube System	☒	☐	☐	
Use Job lube system	☐	☐	☐	
Use shop Vibration Probes, Etc.	☐	☐	☐	
Use Job Vibration Probes, Etc.	☒	☐	☐	
Final Assembly, Maintenance &				
Running Clearance (4.2.1.1.e)	☒	☐	☐	☒
Oil System Cleanliness (4.2.3.2)	☐	☐	☐	
Oil System-Casing Joint				
Tightness (4.3.2.1.4)	☐	☐	☐	
Warning And Protection				
Devices (4.3.2.1.5)	☐	☐	☐	
Seismic Vibration Data (4.3.2.2.3)	☐	☐	☐	☐
Vibration, Phase Plots (4.3.2.2.12)	☒	☐	☐	☒
Oil Inlet Range test (4.3.2.2.13)	☐	☐	☐	☐
Tape recorded Vibration Data	☒	☐	☐	☒
(4.3.2.2.14) (4.3.2.2.15)	☐			Purchaser copy
NON-DESTRUCTIVE TESTING (4.2.1.2) (4.2.2.1)				
	Surface	Sub surface		Log
☐ Casing	☐	☐		☐
☒ Rot. Elemts.	☒	☒		☒
☒ Bearings	☒	☒		☒
☐ Other :	☐	☐		☐
(Specify)				

NOTES : _____

During start-up, gears can exhibit a transient spike reading of vibration levels that will exceed shutdown settings. Therefore a trip multiplier is recommended in the control system.



Mechanical running test duration 4 hours including

- Shaft vibration record using job vibration probes if ordered
- Bearings temperature records
- Casing vibration measurement
- Sound level pressure measurement
- Power losses measurement at oil outlet
- Performed with oil ISO VG 32

Oil flow requirement and power losses are calculated values only, add normal safety margins for sizing heat exchangers.



APPAREIL.xls _ Edition du :06.03.2015
1/1



ADDITIONAL TECHNICAL DATASHEET				Job No. 41104 Item No. A																																																		
				P.O. No. _____ Date _____																																																		
				Requisition No. _____																																																		
				Inquiry No. _____																																																		
				Revision 1 Date 06.03.2016 By HNI																																																		
1	☒ ADDITIONAL GEAR DATA			☐ TURNING GEAR (Dimensioning is preliminary !)																																																		
2	Efficiency			Calculation results																																																		
3	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%;">Percent of rated power</th> <th style="width: 50%;">Efficiency</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">100%</td> <td style="text-align: center;">99,03</td> </tr> <tr> <td style="text-align: center;">75%</td> <td style="text-align: center;">98,92</td> </tr> <tr> <td style="text-align: center;">50%</td> <td style="text-align: center;">98,79</td> </tr> <tr> <td style="text-align: center;">25%</td> <td style="text-align: center;">98,08</td> </tr> <tr> <td style="text-align: center;">10%</td> <td style="text-align: center;">90,80</td> </tr> </tbody> </table>			Percent of rated power	Efficiency	100%	99,03	75%	98,92	50%	98,79	25%	98,08	10%	90,80	Required turning speed _____ rpm Actual turning speed _____ rpm Required breakaway torque _____ Nm Actual breakaway torque _____ Nm Actual maximum torque _____ Nm Actual acceleration time _____ s																																						
Percent of rated power	Efficiency																																																					
100%	99,03																																																					
75%	98,92																																																					
50%	98,79																																																					
25%	98,08																																																					
10%	90,80																																																					
4																																																						
5																																																						
6																																																						
7																																																						
8																																																						
9																																																						
10	Losses			Motor																																																		
11	Power loss at no load _____ kW			Supplier _____																																																		
12	Heat rejection _____ kcal/h			Power _____ kW																																																		
13				Voltage _____ V																																																		
14				Frequency _____ Hz																																																		
15	☐ PUMP DETAILS (Dimensioning is preliminary !)			Speed _____ rpm																																																		
16				Electric standard _____																																																		
17	Design : _____			Turning gear																																																		
18	Speed : _____ rpm			Type _____																																																		
19	Oil flow : _____ l/min			Ratio _____																																																		
20	Oil pressure : _____ bar			Clutch																																																		
21	NPSH : _____ m			Type _____																																																		
22	Safety valve : _____			Max. allowable torque _____ Nm																																																		
23	Driving method : _____			Miscellaneous																																																		
24	Material : _____			Starting device _____																																																		
25	Flanges : _____			Switch details _____																																																		
26	Testing : _____																																																					
27	Furniture of ATEX certificate : _____																																																					
28																																																						
29																																																						
30	☒ INSTRUMENTATION PACKAGE																																																					
31	Thermometer			Thermoelements																																																		
32																																																						
33	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th style="width: 33%;">Bearing</th> <th style="width: 33%;">Thrust bearing</th> <th style="width: 33%;">Oil inlet/outlet</th> </tr> </thead> <tbody> <tr> <td>Qty</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Type</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>				Bearing	Thrust bearing	Oil inlet/outlet	Qty				Type				<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th style="width: 33%;">Bearing</th> <th style="width: 33%;">Thrust bearing</th> <th style="width: 33%;">Oil inlet/outlet</th> </tr> </thead> <tbody> <tr> <td>Type</td> <td>DUPLEX 2x3F</td> <td>DUPLEX 2x3F</td> <td></td> </tr> <tr> <td>Classification</td> <td>IEC60751</td> <td>IEC60751</td> <td></td> </tr> <tr> <td>Removable from the outside</td> <td>NO</td> <td>NO</td> <td></td> </tr> <tr> <td>ATEX</td> <td>ATEX Exia</td> <td>ATEX Exia</td> <td></td> </tr> </tbody> </table>			Bearing	Thrust bearing	Oil inlet/outlet	Type	DUPLEX 2x3F	DUPLEX 2x3F		Classification	IEC60751	IEC60751		Removable from the outside	NO	NO		ATEX	ATEX Exia	ATEX Exia																		
	Bearing	Thrust bearing	Oil inlet/outlet																																																			
Qty																																																						
Type																																																						
	Bearing	Thrust bearing	Oil inlet/outlet																																																			
Type	DUPLEX 2x3F	DUPLEX 2x3F																																																				
Classification	IEC60751	IEC60751																																																				
Removable from the outside	NO	NO																																																				
ATEX	ATEX Exia	ATEX Exia																																																				
34																																																						
35																																																						
36																																																						
37																																																						
38																																																						
39																																																						
40	Shaft vibrations																																																					
41																																																						
42	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th style="width: 20%;">Radial</th> <th style="width: 10%;">HS</th> <th style="width: 10%;">Axial</th> <th style="width: 10%;">LS</th> <th style="width: 20%;">Keyphasor</th> <th style="width: 30%;">Accelerometer</th> </tr> </thead> <tbody> <tr> <td>Type</td> <td>B.N. 3300 XL 8mm Sys. 9M</td> <td></td> <td>No</td> <td></td> <td>B.N. 3300 XL 8mm Sys. 9M</td> <td>ACCELEROMETER BENTLY</td> </tr> <tr> <td>Probe</td> <td>Yes</td> <td></td> <td>No</td> <td></td> <td>Yes</td> <td></td> </tr> <tr> <td>Proximitior</td> <td>Yes</td> <td></td> <td>No</td> <td></td> <td>Yes</td> <td></td> </tr> <tr> <td>Probe holder</td> <td>Yes</td> <td></td> <td>No</td> <td></td> <td>Yes</td> <td></td> </tr> <tr> <td>Connection head</td> <td>Yes</td> <td></td> <td>No</td> <td></td> <td>Yes</td> <td></td> </tr> <tr> <td>mounting kit</td> <td></td> <td></td> <td>Yes</td> <td></td> <td></td> <td>Yes</td> </tr> </tbody> </table>						Radial	HS	Axial	LS	Keyphasor	Accelerometer	Type	B.N. 3300 XL 8mm Sys. 9M		No		B.N. 3300 XL 8mm Sys. 9M	ACCELEROMETER BENTLY	Probe	Yes		No		Yes		Proximitior	Yes		No		Yes		Probe holder	Yes		No		Yes		Connection head	Yes		No		Yes		mounting kit			Yes			Yes
	Radial	HS	Axial	LS	Keyphasor	Accelerometer																																																
Type	B.N. 3300 XL 8mm Sys. 9M		No		B.N. 3300 XL 8mm Sys. 9M	ACCELEROMETER BENTLY																																																
Probe	Yes		No		Yes																																																	
Proximitior	Yes		No		Yes																																																	
Probe holder	Yes		No		Yes																																																	
Connection head	Yes		No		Yes																																																	
mounting kit			Yes			Yes																																																
43																																																						
44																																																						
45																																																						
46																																																						
47																																																						
48																																																						
49																																																						
50																																																						
51																																																						
52																																																						
53																																																						
54																																																						
55	Junction box(es)			Miscellaneous																																																		
56																																																						
57	Qty 0			Identification ☒ wire ☒ conduit ☐ junction box																																																		
58	Manufacturer _____			Conduit type _____																																																		
59	Material _____			Transmitter type _____ Qty _____																																																		
60	ATEX None			Terminal block type _____ Qty _____																																																		
61																																																						

Y/ref : Khursaniyah Al Fadhili - D43-K-3801 -
O/ref : D41104 quotation number 3

ITEM B 1 : Flender Graffenstaden (FG) High Speed increaser, model **TX40/5C**

- *Rating conditions :* Rated power at **1620 kW**
Driven by a electric motor at **1800.0 rpm** (specified : 1800.0 rpm)
Driving a centrifugal compressor at **10737.9 rpm** (specified : 10736.0 rpm)
Service factor **1.47** according to **API613/03** (required : > 1.4)
- *Technical description :* Double helical
Manufacturing according to API standard
Flange on LS shaft end
Flange on HS shaft end
Estimated Weight : 1900 kg
- *Bearings description :* 2 cylindrical bearings on LS shaft
2 tilting pads bearings on HS shaft
1 double acting tilting pad thrust bearing on low speed shaft non driven end
- *Mechanical running test :* Full speed, no load test during 4 hours according to the API 613 5th Edition standard.
- *Lubrication conditions :* 64 l/min of Oil ISO VG 46 at 60°C and 2.5 bar at inlet (calculated values only)
- *Miscellaneous:* Efficiency at full load : 98.70 %
Power losses at full load : 21 kW (calculated value only)
Anticipated Sound Pressure Level: 82.0 ± 2dB(A) at 1 meter

Base price : **103 850 EUR** each gear box

Delivery time : **36 weeks** after the FG acknowledgement of the order

Quantity : **1 gearbox**

Comments :

- Coupling data taken into account on HS Shaft:
 - o Weight: 10.4 kg
 - o Center of gravity position from shaft end: 28.2 mm
 - o Inertia: 0.104 kgm²
- Coupling data taken into account on LS Shaft:
 - o Weight: 26.4 kg
 - o Center of gravity position from shaft end: 30.9 mm
 - o Inertia: 0.264 kgm²

Including :

- Customer witness of test
- After test disassembly and inspection
- Noise level test report
- Lateral analysis undamped
- Documentation : downloadable electronic file in English

Instrumentation (see the complete package on additional technical data sheet):

- *Temperature package*
12 RTD's PT100 Duplex 3 wires from Thermo Electric Company Inc.
(2 per bearing and thrust bearing side) not wired with terminal heads..... Price included
- *Bently Nevada vibration package*
8 radial (4 per shaft) & 2 axial (on LS shaft) vibration probes, 2 accelerometers (1 per shaft), 2 keyphasors (1 per shaft) not wired Price included

Spare parts (Prices are net valid only if spares are ordered together with the gearbox):

- *Commissioning Spares*
2 RTD's, 2 BN vibration probes, 2 BN accelerometers 7 900 EUR Lot Net
- *2 Years Normal Operation Spares*
1 set of bearings with RTD's, 1 set of oil seals 26 010 EUR Lot Net
- *Strategic Spare Parts*
One complete set of rotating elements consisting of one pinion and one gear.
Tested if ordered together with the main gearbox according to API613/03
Full Speed, No Load, with Test Report..... 37 100 EUR Lot Net
- *Container for horizontal spare rotors storage painted according FG standard*..... 15 850 EUR Lot Net

SPECIAL PURPOSE GEAR UNITS
API 613 FIFTH EDITION
DATA SHEET SI UNITS

1 Applicable To: ☒ Proposal ☐ Purchase ☐ As Built 2 For <u>Siemens AG Dulsburg</u> 3 Site <u>Khursaniyah Al Fadhlili</u> 4 Unit <u>STC-SV 06-3-A</u> 5 Service <u>EM/CC</u> 6 No. required <u>1</u>	Job No. <u>41104</u> Item No. <u>B</u> P.O. No. _____ Date _____ Requisition No. _____ Inquiry No. _____ Revision <u>1</u> Date <u>06.03.2015</u> By <u>HNI</u> ☐ US Standards (1.7) ☒ ISO Standards (1.7)
7 NOTE : Numbers within () refer to applicable API standard 613 paragraphs 8 ☐ Information To be completed by purchaser ☐ Information to be completed by manufacturer	
9 ○ UNITS OF MEASUREMENT 10 ☐ US Customary units 11 ☒ SI units 12 ○ RATING REQUIREMENTS 13 Driven equip. (2.1.4): Norm. _____ Max _____ kW 14 Driver: Rated _____ Max _____ kW 15 Normal transmitted power (2.2.2) _____ kW 16 Gear unit rated power (2.2.1) <u>1620</u> kW 17 Torque @ max cont speed _____ Nm 18 Max torque (2.2.1) _____ Nm @ _____ rpm 19 ☐ Reducer ☒ Increaser 20 Rated speed (2.1.5): 21 Input <u>1800</u> rpm ☐ Specified ☒ Nominal 22 Output <u>10736</u> rpm ☐ Specified ☒ Nominal 23 Allow var in gear ratio (2.1.5) (+) (-) _____ % 24 Max continuous speed (1.5) <u>1800 / 10736</u> rpm 25 Trip speed (1.5) (2.1.7) <u>1980 / 11809,6</u> rpm 26 Gear service factor (2.2.3.1) <u>1,4 API 613/2003 5 TH</u> (min) 27 Hardness (2.2.3.2) Pinion _____ Gear _____ 28 Shaft assembly designation (2.1.10) <u>L/R</u> 29 HS shaft rot fac'g cpl'g (2.1.20.2) ☒ CW ☐ CCW 30 LS shaft rot fac'g cpl'g (2.1.20.2) ☒ CW ☐ CCW 31 External loads (2.1.16) _____ 32 Other operating conditions (2.2.2) (2.6.1.3) _____	10 ■ BASIC GEAR DATA 11 ☒ Single stage ☐ Single helical 12 ☐ Double stage ☒ Double helical 13 ☐ Epicyclic ☐ <u>horizontal offset</u> 14 Mechanical rating (1.5.16) <u>2268</u> kW @ <u>1800 / 10737,9</u> rpm 15 Gear service factor (2.2.3.1) <u>1,46 API 613/2003 5 TH</u> (actual) 16 Full load gear unit power loss <u>21</u> kW 17 Gear Unit Mechanical efficiency <u>98,70</u> % 18 Rating speed Pinion <u>10.737,9</u> Gear <u>1.800,0</u> rpm 19 Hardness used for 20 Rating, (HB or Rc) Pinion <u>58 HRC</u> Gear <u>58 HRC</u> 21 Tooth pitting index, "K" (2.2.4.1) (2.2.4.2) 22 Allowable <u>2,17</u> Actual <u>2,06</u> MPa 23 Material index number (Fig 3, Table 4) <u>3,03</u> MPa 24 Bending stress number, "S_t" (2.2.5.1) (2.2.5.2) 25 Pinion: Allowable <u>265,4</u> Actual <u>251,0</u> MPa 26 Gear: Allowable <u>265,4</u> Actual <u>238,8</u> MPa 27 Pitch line velocity <u>63,0</u> m/s 28 Anticipated SPL (2.1.6) <u>82</u> dB(A) @ <u>1</u> m 29 WR² referred to LS shaft <u>29,88</u> kgm² 30 Breakaway torque <u>90</u> Nm @ LS Shaft 31 Pinion teeth hardness range <u>58 - 63 HRC</u> 32 Pinion teeth hardening method <u>CARBURIZED</u> 33 ☐ HS shaft separate hardness range _____ 34 Gear teeth (rim) hardness range <u>58 - 63 HRC</u> 35 Gear teeth hardening method <u>CARBURIZED</u> 36 Gear hub: 37 ☒ Forged cylinder ☐ Forged & Capped ☐ Fabricated 38 Gear to Shaft fit method (2.5.3.2) 39 ☐ Integral ☐ Keyed interference ☒ Keyless interference 40 Rim attachment (2.5.3.2) <u>FORGED GEAR WHEEL</u> 41 LS shaft hardness range <u>HB 230 - 274</u> 42 Journal static weight loads (2.6.6.3) 43 Pinion <u>37</u> / <u>4</u> kg Gear <u>347</u> / <u>253</u> kg 44 Total gear unit assembled weight <u>1900</u> kg 45 NOTES: _____ 46 _____ 47 _____ 48 _____ 49 _____ 50 _____
35 ○ INSTALLATION DATA (2.1.14) 36 ☐ Indoor ☐ Heated ☐ Under roof 37 ☒ Outdoor ☐ Unheated ☐ Partial sides 38 ☐ Grade ☐ Mezzanine ☒ ONSHORE 39 ☐ Winterization required ☐ Tropicalization required 40 Electrical area (2.1.10) Class _____ Grp _____ Div _____ 41 Electrical area (2.1.10) Zone <u>2</u> Grp <u>IIA</u> Temp <u>T1</u> °C 42 Max allow SPL (2.1.6) _____ dB(A) @ _____ m 43 Elevation _____ m Barometer _____ kPa abs 44 Range of ambient temperatures: 45 Dry bulb _____ °C Wet bulb _____ °C 46 Normal _____ °C _____ °C 47 Maximum <u>82</u> °C _____ °C 48 Minimum <u>0</u> °C _____ °C 49 Unusual conditions ☐ Dust ☐ Fumes 50 ☐ _____	

SPECIAL PURPOSE GEAR UNITS
API 613 FIFTH EDITION
DATA SHEET SI UNITS

Job No.	41104	Item No.	B
P.O. No.		Date	
Requisition No.			
Inquiry No.			
Revision	1	Date	06.03.2015 By HNI

■ GEAR DATA				○ COUPLINGS AND GUARDS		
	Pinion	Gear		Pinion	Gear	
Number of teeth	29	173	Coupling furnished by (3.2.1)	Compr. Supplier	Compr. Supplier	
Gear ratio	5,97		Mount coupling halves (3.2.2)	Compr. Supplier	Compr. Supplier	
Tangential load, "Wt" (2.2.4.2)	25.731	N	Cplg. guard adapter by (3.2.3)	Gear Supplier	Gear Supplier	
AGMA Geometry factor "J"	0,52	0,54	Cplg. guard furnished by (3.2.3)	Compr. Supplier	Compr. Supplier	
Pitch diameter	111,98	668,02	Coupling vendor (3.2.3)			
Outside diameter	120,30	673,50	Vendor's model number (3.2.3)			
Root diameter	103,05	656,32	Coupling weight on shaft, kg	10,4	26,4	
Center groove diameter	93,00	640,00	CG Inboard / outboard of shaft end	Outboard	Outboard	
Normal pressure angle	20,00	deg	Hub drill template provided	☐	☐	
Normal diametral pitch	7,26	in ⁻¹	■ SHAFT END DETAIL (2.5.4.2)			
Helix angle	24,25	deg	Shaft end detail specified by: ☒ Purchaser ☐ Gear vendor			
Center distance	390,00	mm	(Integral unless otherwise specified)			
Backlash min	0,28	mm	Shaft end detail if 'otherwise' specified:			
Net face width, "Fw"	130,00	mm	Pinion	Gear		
Pinion L/D	1,74		Tapered / Keyless	☐ ☐	☐ ☐	
Face overlap ratio	4,86		Tapered / 1-Key	☐ ☐	☐ ☐	
Transverse contact ratio	1,45		Tapered / 2-Keys	☐ ☐	☐ ☐	
AGMA 6011 service factor	2,87		Cylindrical / 1-Key	☐ ☐	☐ ☐	
Rating based on ANSI/AGMA 6011 with SF=1,0			Cylindrical / 2-Keys	☐ ☐	☐ ☐	
Durability Power	5404	kW	Other <u>Flanged</u>	☒ ☐	☒ ☐	
Strength Power	4652	kW	Shaft diameter	75,0	120,0	
Tooth Surface Finish, Ra	0,4	µm	(If integral flange use diameter immediately adjacent to flange)			
Tooth Generation Process	Hobbing	Hobbing	■ RADIAL BEARINGS			
Tooth Finishing Process	Grinding	Grinding	Type	Pinion	Gear	
Lead modification (2.2.4.6)	☒ Not Req'd	☐ Req'd		T.PADS / T.PADS	CYL. / CYL.	
Calculated Total Lead Mismatch		µm	Diameter	80 / 80	120 / 120	
■ SCUFFING DATA (2.2.6)			Length	56 / 56	60 / 60	
Scuffing Data per ANSI/AGMA 925-A03			Journal velocity	45,0 / 45,0	11,3 / 11,3	
Scuffing Risk (2.2.6) <u><=5% (Low)</u>	Calculation Method	AGMA925	Loading	3,08 / 3,10	2,52 / 2,26	
Composite surface roughness, ox	0,57	µm	Clearance (min-max)			
Specific film thickness, EHL Amin	2,54	µm	Span	340	340	
Tooth temperature, 0m	80	°C	Power loss each bearing	6,3 / 6,3	0,7 / 0,7	
Maximum contact temperature, 0Bmax	93	°C	Oil flow each bearing	15,0 / 15,0	5,0 / 5,0	
■ MATERIALS			■ THRUST BEARINGS			
Gear casing	Steel	Oil seals	aluminum	Location	OPP.CPLG.SIDE	
Pinion(s)	18CrNiMo7-6			Manufacturer	FLENDER	
Gear rim(s)	18CrNiMo7-6			Type	NO	
HS Shaft	Integral	LS Shaft	42CrMo4	Size	COMB.TAP.LANDS	
Radial bearings	Babbitt	Backing	Steel	Area	5160	
Thrust bearing(s)	Babbitt	Backing	Steel	Loading	1,35	
○ SHAFT END DETAIL			Rating	1,50	MPa	
☒ Gear shaft end for coupling integral flange (2.5.4.2)			Int. thrust load		N	
☒ Pinion shaft end for coupling integral flange (2.5.4.2)			Ext. thrust load	2.700	N	
☒ Other : <u>WITHOUT BOLTS</u>			Power loss each	0,0	kW	
			Oil flow each bearing	0,0	l/min	
			NOTES :			

SPECIAL PURPOSE GEAR UNITS
API 613 FIFTH EDITION
DATA SHEET SI UNITS

1 ○ LUBRICATION REQUIREMENTS 2 ☐ Oil system furnished by (2.8.3) _____ 3 ☐ Other _____ ☐ Gear vendor _____ 4 ☐ Oil visc. _____ cp @ 40°C _____ cp @ 100°C (2.8.6) 5 ☐ ISO Grade _____ Load stage (2.2.6) 7,0 6 7 ■ MESH 8 Mesh and windage power loss 2,0 kW 9 Oil flow, mesh 9,0 l/min 10 11 ■ LUBRICATION REQUIREMENTS 12 Min. startup oil temperature 20,0 °C 13 Normal oil inlet temperature 60,0 °C 14 Maximum oil inlet temperature 65,0 °C 15 Unit oil flow (total) 64,0 l/min 16 Unit oil pressure 2,5 bar 17 ☐ Oil visc. _____ cp @ 40°C _____ cp @ 100°C (2.8.6) 18 ☐ ISO Grade 46 Load stage (2.2.6) 7,0 19 20 ■ PIPING CONNECTIONS <table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>Service</th> <th>No.</th> <th>Size</th> <th>Type</th> </tr> <tr> <td>Lube oil inlet</td> <td>1</td> <td>1,5 in.</td> <td>ANSI 150 LBS</td> </tr> <tr> <td>Lube oil outlet</td> <td>1</td> <td>6 in.</td> <td>ANSI 150 LBS</td> </tr> <tr> <td>Casing drain *</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Vent</td> <td>1</td> <td>1,5 in.</td> <td>ANSI 150 LBS</td> </tr> <tr> <td>Casing purge</td> <td></td> <td></td> <td></td> </tr> </table> 27 * Casing drain is 'dead bottom' housing drain, not lube oil outlet 28 ○ MOUNTING PLATES 29 ☐ Gear furnished with (3.3.1.1) 30 ☐ Baseplate ☐ Soleplate ☐ Subplate(s) (3.3.2.10) 31 ☐ Mounting plates(s) furnished by (3.3.1.1) _____ 32 ☐ Baseplate leveling (3.3.2.3) _____ 33 ☐ Baseplate with leveling pads (3.3.2.3) 34 ☐ Baseplate suitable for column mounting (3.3.2.4) 35 ☐ Vendor review of purchaser's foundation dwgs. (2.1.13) 36 ☐ Grout type (3.3.1.2.4) _____ 37 38 ○ CONTRACT DATA 39 ☐ Test data prior to shipment _____ 40 ☒ Progress report (5.3.3) _____ 41 ☐ Vendor signoff of inspector checklist (4.1.1.3) 42 ☒ Information retained for 20 years (4.2.1.1) (4.2.2.6.1) 43 ☐ Technical manual (5.3.5.4) 44 ☒ PAINTING (4.4.3.1) ☒ Flender standard RAL5015 (blue) 45 ☒ Painting housing interior not allowed (2.3.1.14) 46 ○ SHIPMENT 47 ☐ Steel rotor storage container (4.4.5) ☐ Shaft covers (4.4.4) 48 <table style="width:100%;"><tr><td></td><td>Contract unit</td><td>Spares</td></tr><tr><td>Export boxing</td><td>☐</td><td>☐</td></tr><tr><td>Domestic boxing</td><td>☐</td><td>☐</td></tr><tr><td>Outdoor storage over 6 mos.</td><td>☐</td><td>3 years indoor ☐ (4.4.3.9)</td></tr></table>	Service	No.	Size	Type	Lube oil inlet	1	1,5 in.	ANSI 150 LBS	Lube oil outlet	1	6 in.	ANSI 150 LBS	Casing drain *				Vent	1	1,5 in.	ANSI 150 LBS	Casing purge					Contract unit	Spares	Export boxing	☐	☐	Domestic boxing	☐	☐	Outdoor storage over 6 mos.	☐	3 years indoor ☐ (4.4.3.9)	Job No. 41104 Item No. B P.O. No. _____ Date _____ Requisition No. _____ Inquiry No. _____ Revision 1 Date 08.03.2015 By HNI ○ ADDITIONAL REQUIREMENTS ○ VIBRATION DETECTORS RADIAL (3.4.2.1) (2.7.4.5) (2.7.4.6) ☒ Manufacturer BENTLY NEVADA ☒ Total No. 8 ☒ X-Y probes pinion bearings ☒ Coupling end ☒ Blind end ☒ X-Y probes gear bearings ☒ Coupling end ☒ Blind end ☐ Other _____ AXIAL (3.4.2.1) (2.7.4.5) (2.7.4.6) ☒ Manufacturer BENTLY NEVADA ☒ Total No. 2 ☐ Dual probes at each thrust bearing ☐ Single probe any shaft without thrust bearing ☐ Other _____ ONE EVENT PER REVOLUTION PROBE (2.7.4.5) (2.7.4.6) ☒ Manufacturer BENTLY NEVADA Total No. 2 ☒ One on input shaft ☒ One on output shaft ☐ Other _____ ACCELEROMETER (3.4.2.1) (2.7.4.5) (2.7.4.6) ☒ Manufacturer BENTLY NEVADA ☒ No. required 2 ☒ Pinion coupling end ☒ Gear coupling end ☐ Other _____ ○ TEMPERATURE DETECTORS ☐ Dial type thermometers (3.4.2.7) _____ ☒ Type brg. temp. sensors (3.4.2.7) (2.7.1.3) PT100 ☐ RTD ☐ Thermocouple / ☐ Simplex ☒ Duplex Calibration Yes ☒ HSALS bearings no. sensors each 2 / 2 ☒ Thrust number of sensing elements each face 2 ○ OTHER VIBRATION AND TEMPERATURE (3.4.2.5) (3.4.2.6) Other Gear vendor Oscillator demodulator supplied by ☐ ☒ Vibration monitor supplied by ☒ ☐ ☐ Vibration shutdown delay time _____ seconds Temperature monitor supplied by ☒ ☐ Oscillator demodulator J-box by ☒ ☐ Temp. sensor termination J-box by ☒ ☐ J-box type _____ Mount _____ ○ MISCELLANEOUS ☒ Undamped critical analysis report (2.6.2.1) ☐ w/ damped rotor response analysis report (2.6.2.4.3) (2.6.2.6) Torsional analysis by (2.6.5.2) ☐ Gear vendor ☒ Other ☒ Spare set of gear rotors (4.3.2.4) ☐ Gear case furnished with inlet purge connection (2.4.3) ☐ Orientation of oil inlet & drain conns. (2.4.6) ☒ Filter breather location (2.3.1.12) Prov. on upper casing ☐ Torsional device provisions (2.5.4.5) ☐ Rotor vertical storage provisions (2.5.4.8) ☐ Rotor vertical storage fixture(s) (3.6.2) ☐ Vendor service rep. on site (2.1.13)
Service	No.	Size	Type																																		
Lube oil inlet	1	1,5 in.	ANSI 150 LBS																																		
Lube oil outlet	1	6 in.	ANSI 150 LBS																																		
Casing drain *																																					
Vent	1	1,5 in.	ANSI 150 LBS																																		
Casing purge																																					
	Contract unit	Spares																																			
Export boxing	☐	☐																																			
Domestic boxing	☐	☐																																			
Outdoor storage over 6 mos.	☐	3 years indoor ☐ (4.4.3.9)																																			

SPECIAL PURPOSE GEAR UNITS
API 613 FIFTH EDITION
DATA SHEET SI UNITS

Job No. 41104 Item No. B
P.O. No. _____ Date _____
Requisition No. _____
Inquiry No. _____
Revision 1 Date 06.03.2015 By HNI

O INSPECTIONS AND TESTS (4.1)				
☐ Advance notice of witness testing required (4.1.3) Number calendar days _____				
	Req'd	Witness	Observe	Test Log
6	Shop Inspection (4.1.1)	☐	☐	☐
7	Cleanliness Inspection (4.2.3.1)	☐	☐	☐
8	Hardness Verification (4.2.3.3)	☒	☐	☒
9	Dismantle-reassembly (4.3.2.3.1)	☒	☐	☐
10	Contact Check (2.5.2.2)	☒	☐	☐
11	Contact Check Tape Lift (2.5.2.2)	☒	☐	☒
12	Gear accuracy check (2.5.2.1)	☒	☐	☐
13	Double helical axial stability (2.5.2.3)	☒	☐	☒
14	Special testing integral forged gears (2.5.3.3)			
15	(testing per mutual agreement)	☐	☐	☐
16	Residual unbalance check (2.6.6.2)	☒	☐	☒
17	Mechanical Run Test (Main) (4.3.2)	☒	☐	☒
18	Mechanical Run Test (Spare) (4.3.2.4)	☐	☐	☐
19	Adm. Mechanical Tests (4.3.2.2.16)	☐	☐	☐
20	Part or Full Load And Full Speed			
21	Test (4.3.3.1)	☐	☐	☐
22	Full torque, reduced speed (4.3.3.2)	☐	☐	☐
23	Full Torque Static Test (4.3.3.3)	☐	☐	☐
24	Back-To-Back Locked Torque			
25	Test (4.3.3.4)	☐	☐	☐
26	Sound Level Test (4.3.3.5)	☒	☐	☒
27	Additional gear tooth test (4.2.2.8)	☐	☐	☐
28	Use shop Lube System	☒	☐	☐
29	Use job lube system	☐	☐	☐
30	Use shop Vibration Probes, Etc.	☐	☐	☐
31	Use job Vibration Probes, Etc.	☒	☐	☐
32	Final Assembly, Maintenance &			
33	Running Clearance (4.2.1.1.e)	☒	☐	☒
34	Oil System Cleanliness (4.2.3.2)	☐	☐	☐
35	Oil System-Casing Joint			
36	Tightness (4.3.2.1.4)	☐	☐	☐
37	Warning And Protection			
38	Devices (4.3.2.1.5)	☐	☐	☐
39	Seismic Vibration Data (4.3.2.2.3)	☐	☐	☐
40	Vibration, Phase Plots (4.3.2.2.12)	☒	☐	☒
41	Oil Inlet Range test (4.3.2.2.13)	☐	☐	☐
42	Tape recorded Vibration Data	☒	☐	☒
43	(4.3.2.2.14) (4.3.2.2.15)	☐	Purchaser copy	
44	NON-DESTRUCTIVE TESTING (4.2.1.2) (4.2.2.1)			
	Surface	Sub surface	Log	
46	☐ Casing	☐		☐
47	☒ Rot. Elmts.	☒		☒
48	☒ Bearings	☒		☒
49	☐ Other :	☐		☐
50	(Specify)			

NOTES : _____

During start-up, gears can exhibit a transient spike reading of vibration levels that will exceed shutdown settings. Therefore a trip multiplier is recommended in the control system.

Mechanical running test duration 4 hours including

- Shaft vibration record using job vibration probes if ordered
- Bearings temperature records
- Casing vibration measurement
- Sound level pressure measurement
- Power losses measurement at oil outlet
- Performed with oil ISO VG 32

Oil flow requirement and power losses are calculated values only, add normal safety margins for sizing heat exchangers.

PRELIMINARY MASS ELASTIC DATA

Customer : Siemens AG Duisburg
Destination : Khursaniyah Al Fadhl
Purchaser order :
F-G job number : D 4110481 OL:
Type and serial N° : TX40/5C



Power rating : 1620 kW
Service factor : $AP1613.03 \times \approx 1,4$
Input speed : 1800 rpm
Output speed : 10737,9 rpm
Speed ratio : 5,96

Weight HSS : 30,5 kg
Weight pos. from teeth middle HSS : 57,5 mm
Inertia HSS : 0,038 Kg.m²
Stiffness HSS : 1,11 MN/mrd
Bearing type 1 : Tilting pads 80 x 56
Bearing type 2 : Tilting pads 80 x 56
Add. weight on brg. side 1 : 10,4 kg

Weight LSS : 574,3 kg
Weight pos. from teeth middle LSS : 9 mm
Inertia LSS : 28,526 Kg.m²
Stiffness LSS : 6,5 MN/mrd
Bearing type 4 : Cylindrical 120 x 60
Bearing type 3 : Cylindrical 120 x 60
Add. weight on brg. side 4 : 26,4 kg

Positive direction of external

APPAREIL.xls _ Edition du :06.03.2015
1/1



ADDITIONAL TECHNICAL DATASHEET				Job No. <u>41104</u> Item No. <u>B</u>																																											
				P.O. No. _____ Date _____																																											
				Requisition No. _____																																											
				Inquiry No. _____																																											
				Revision <u>1</u> Date <u>06.03.2015</u> By <u>HNI</u>																																											
☒ ADDITIONAL GEAR DATA			☐ TURNING GEAR (Dimensioning is preliminary I)																																												
<i>Efficiency</i>			<i>Calculation results</i>																																												
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%;">Percent of rated power</th> <th style="width: 50%;">Efficiency</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">100%</td> <td style="text-align: center;">98,70</td> </tr> <tr> <td style="text-align: center;">75%</td> <td style="text-align: center;">98,66</td> </tr> <tr> <td style="text-align: center;">50%</td> <td style="text-align: center;">98,38</td> </tr> <tr> <td style="text-align: center;">25%</td> <td style="text-align: center;">97,42</td> </tr> <tr> <td style="text-align: center;">10%</td> <td style="text-align: center;">87,68</td> </tr> </tbody> </table>			Percent of rated power	Efficiency	100%	98,70	75%	98,66	50%	98,38	25%	97,42	10%	87,68	Required turning speed _____ rpm Actual turning speed _____ rpm Required breakaway torque _____ Nm Actual breakaway torque _____ Nm Actual maximum torque _____ Nm Actual acceleration time _____ s																																
Percent of rated power	Efficiency																																														
100%	98,70																																														
75%	98,66																																														
50%	98,38																																														
25%	97,42																																														
10%	87,68																																														
<i>Losses</i>			<i>Motor</i>																																												
Power loss at no load _____ kW Heat rejection _____ kcal/h			Supplier _____ Power _____ kW Voltage _____ V Frequency _____ Hz Speed _____ rpm Electric standard _____																																												
☐ PUMP DETAILS (Dimensioning is preliminary I)			<i>Turning gear</i>																																												
Design : _____ Speed : _____ rpm Oil flow : _____ l/min Oil pressure : _____ bar NPSH : _____ m Safety valve : _____ Driving method : _____ Material : _____ Flanges : _____ Testing : _____ Furniture of ATEX certificate : _____			Type _____ Ratio _____																																												
			<i>Clutch</i>																																												
			Type _____ Max. allowable torque _____ Nm																																												
			<i>Miscellaneous</i>																																												
			Starting device _____ Switch details _____																																												
☒ INSTRUMENTATION PACKAGE																																															
<i>Thermometer</i>			<i>Thermoelements</i>																																												
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th style="width: 33%;">Bearing</th> <th style="width: 33%;">Thrust bearing</th> <th style="width: 33%;">Oil inlet/outlet</th> </tr> </thead> <tbody> <tr> <td>Qty</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Type</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>				Bearing	Thrust bearing	Oil inlet/outlet	Qty				Type				<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th style="width: 33%;">Bearing</th> <th style="width: 33%;">Thrust bearing</th> <th style="width: 33%;">Oil inlet/outlet</th> </tr> </thead> <tbody> <tr> <td>Type</td> <td>DUPLEX 2x3F</td> <td>DUPLEX 2x3F</td> <td></td> </tr> <tr> <td>Classification</td> <td>IEC60751</td> <td>IEC60751</td> <td></td> </tr> <tr> <td>Removable from the outside</td> <td>NO</td> <td>NO</td> <td></td> </tr> <tr> <td>ATEX</td> <td>ATEX Eexia</td> <td>ATEX Eexia</td> <td></td> </tr> </tbody> </table>				Bearing	Thrust bearing	Oil inlet/outlet	Type	DUPLEX 2x3F	DUPLEX 2x3F		Classification	IEC60751	IEC60751		Removable from the outside	NO	NO		ATEX	ATEX Eexia	ATEX Eexia											
	Bearing	Thrust bearing	Oil inlet/outlet																																												
Qty																																															
Type																																															
	Bearing	Thrust bearing	Oil inlet/outlet																																												
Type	DUPLEX 2x3F	DUPLEX 2x3F																																													
Classification	IEC60751	IEC60751																																													
Removable from the outside	NO	NO																																													
ATEX	ATEX Eexia	ATEX Eexia																																													
<i>Shaft vibrations</i>																																															
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th style="width: 25%;">Radial</th> <th style="width: 10%;">HS</th> <th style="width: 10%;">Axial</th> <th style="width: 10%;">Keyphasor</th> <th style="width: 10%;">Accelerometer</th> </tr> </thead> <tbody> <tr> <td>Type</td> <td>B.N. 3300 XL 8mm Sys. 9M</td> <td>LS</td> <td>No</td> <td>B.N. 3300 XL 8mm Sys. 9M</td> <td>ACCELEROMETER BENTLY</td> </tr> <tr> <td>Probe</td> <td>Yes</td> <td>LS</td> <td>No</td> <td>Yes</td> <td></td> </tr> <tr> <td>Proximitior</td> <td>Yes</td> <td>LS</td> <td>Yes</td> <td>Yes</td> <td></td> </tr> <tr> <td>Probe holder</td> <td>Yes</td> <td>LS</td> <td>Yes</td> <td>Yes</td> <td></td> </tr> <tr> <td>Connection head</td> <td>Yes</td> <td>LS</td> <td>Yes</td> <td>Yes</td> <td></td> </tr> <tr> <td>mounting kit</td> <td></td> <td>LS</td> <td>Yes</td> <td></td> <td>Yes</td> </tr> </tbody> </table>							Radial	HS	Axial	Keyphasor	Accelerometer	Type	B.N. 3300 XL 8mm Sys. 9M	LS	No	B.N. 3300 XL 8mm Sys. 9M	ACCELEROMETER BENTLY	Probe	Yes	LS	No	Yes		Proximitior	Yes	LS	Yes	Yes		Probe holder	Yes	LS	Yes	Yes		Connection head	Yes	LS	Yes	Yes		mounting kit		LS	Yes		Yes
	Radial	HS	Axial	Keyphasor	Accelerometer																																										
Type	B.N. 3300 XL 8mm Sys. 9M	LS	No	B.N. 3300 XL 8mm Sys. 9M	ACCELEROMETER BENTLY																																										
Probe	Yes	LS	No	Yes																																											
Proximitior	Yes	LS	Yes	Yes																																											
Probe holder	Yes	LS	Yes	Yes																																											
Connection head	Yes	LS	Yes	Yes																																											
mounting kit		LS	Yes		Yes																																										
<i>Junction box(es)</i>			<i>Miscellaneous</i>																																												
Qty <u>0</u> Manufacturer _____ Material _____ ATEX <u>None</u>			Identification ☒ wire ☒ conduit ☐ junction box Conduit type _____ Transmitter type _____ Qty _____ Terminal block type _____ Qty _____																																												

Commercial Conditions

- Prices are quoted FCA Illkirch-Graffenstaden following Incoterms 2010 including packing cat 1A of SEI, 1999 issue, ind. 2.
- Progress payments : 100% at delivery.
- This quotation is subjected to the Flender Graffenstaden Standard Terms and Conditions of Sales and valid for acceptance until the 15th of July 2015.
- Where approval of drawings is required, approval must be in line with the document schedule.
- Warranty period is 18 months of operation or 24 months after delivery whichever occurs first. We recommend the supervision of our engineer for the commissioning.
- Flender-Graffenstaden SAS shall not be obligated to fulfill this agreement if such fulfillment is prevented by any impediments arising out of national or international foreign trade or customs requirements or any embargoes or other sanctions.


Applicable documents for the quotation (available on demands)

Documents schedule,
Quality plan
Painting standard,
Standard Terms and Conditions of Sales

We thank you for the opportunity of quoting and look forward to the pleasure of serving you.

Very truly yours,

N. HOST
(Project Engineer)



Y. FRIEDMANN
(Sales Manager)



Generated with CAMEC V 4.9.5 26 Feb 2014

**** "This quotation is subject to confidentiality. Information thereof may not be shared with or forwarded to any third parties!"**